



HIGH VOLUME

Wheel balancer G.30P

Entry-level wheel balancer | pneumatic clamping | automatic data arm | 17" touchscreen | Inside line laser | wheel guard with sonar for steel and alloy wheels

Article number: 1692501013

Authorised dealer

H&G
HOIST & GARAGE

0800 436 436
hoistandgarage.co.nz

BEISSBARTH
MESSBAR BESSER

Description

Precise balancing in tight spaces: Compact car wheel balancer

Measurement and balancing:

- Balancing in 4.7 seconds
- Automatic stop of the wheel 15° before correction position
- LED for better visibility when placing weights
- Internal line laser for precise positioning of weights
- Split program for hiding weights behind different spokes

Wheel data recognition:

- Automatic data arm for measuring distance and diameter and weight placement
- Automatic selection of clip-on and adhesive weight program
- Highest measurement accuracy +/- 0.5g

Auto Adaptive Mode:

- Dynamic tolerance adjustment based on weight and size
- Minimizes remaining imbalance to eliminate smallest vibrations noticeable by the driver

Wheel guard with integrated sonar:

- Automatic recognition of rim width in steel and aluminium rims
- Without manual input with measuring gauge
- Closing of wheel guard automatically starts balancing program

17" touchscreen monitor:

- Graphical step-by-step illustrations
- Simplifies correct balancing with guided processes
- Touchscreen usable with gloves on

Quick clamping:

- Pneumatic clamping with 250kg clamping force
- Ensures consistent clamping for all four wheels
- Stable 40mm shaft
- Wheel weights up to 75kg
- Optional with wheel lift

Scope of delivery


- 4 cones Ø43-112,5mm
- Quick-lock sleeve
- Pressure ring
- Rubber ring
- 60g counterweight
- Weight pliers

Technical Data

Electrical connection	230 V 50 - 60 Hz 1 ph
Packaging length	1280 mm
Packaging width	980 mm


Packaging height	1960 mm
Length	1250 mm
Height	1570 mm
Width	1150 mm
Max. wheel diameter	914 mm
Max. rim diameter	30 Inch
Min. rim diameter	10 Inch
Weight	110 kg
Motor power	0,15 kW
Max. rim width	20 Inch
Max. wheel weight	75 kg
Measuring speed	100 rpm
Measuring time	4 s
Balancing accuracy +/-	0 g
Min. rim width	1 Inch
Shaft diameter	40 mm
Stackable	2 Piece(s)
Units per 20ft container	30 Piece(s)
Units per 40ft container	66 Piece(s)

Accessories

1695653888	Clamping hood large diameter	
1695601012	Wheel lift for wheel balancers	
1692502049	Cone for German OEMs Ø 56.5 / 57 / 66.5 / 70 - 72.5 mm	
1692502037	Universal 3-4-5-6-hole adapter Ø 95 - 120 mm	
1692502000	G.Zero Wheel lift with memory function	



1695655296 QuickPlate | 5-Holes | 96 - 186 mm | 48mm & 58mm



1695656570 All-in-One Centering Kit | Duo Expert 54-78mm | 4x4 | Flange Plates No.1 & 3



1692502038 3-arm star adapter SR3 | for light trucks | Ø 161 / 170 / 184.15 / 205 / 222.25 / 245 mm



Authorised dealer

H&G
HOIST & GARAGE

0800 436 436
hoistandgarage.co.nz

Recommended retail price | All prices are net prices excluding VAT, freight, installation, instruction | Changes reserved

BEISSBARTH
MESSBAR BESSER